GREWIN INDUSTRIAL GROUP CO.,LTD.
TEL/WhatsApp: +86 18622096679
Mail: admin@coilwindingmachinechina.com
Web:www.coilwindingmachinechina.com

Fully Automatic difference Winding machine with step-height GWZ-028DH

SPECIFICATION:

GREWIN INDUSTRIAL GROUP CO.,LTD.

GREWIN INDUSTRIAL GROUP CO.,LTD.
TEL/WhatsApp: +86 18622096679
Mail: admin@coilwindingmachinechina.com
Web:www.coilwindingmachinechina.com

Equipment Parameters

No.	Item	Brand	Remarks
1	Motor	Leadshine	2 sets of servo motors + 1 set of stepping motor
2	Linear Guide	HIWIN	8 pcs
3	Linear Module	HIWIN	1 pcs
4	Air Cylinder	AIRTAC, TOPAIR	14 pcs
5	Display Screen	Kunlun Tongtai	1 pc
6	Solenoid Valve	SENKUAN	1 pc
7	Vibratory Feeder	YOUCHUANGHU	1 pc
8	Power Supply	Mean Well	220V, 8A
9	Cutter	VELISH	1 pc
10	Timing Belt	BANDO	2 pcs
11	Air Source	Air compressor supply	0.4~0.6 MPa
12	Machine Frame	Custom-made	Iron + Aluminum
13	Control System	Delta	1 set
14	Power Rating	3.3 KW	Max. power: 2.15 KW
15	Power Consumption	kWh/h	0.2
16	Dimension (cm)	—	L94 × W76 × H260
17	Weight (KG)	—	300 KG

GREWIN INDUSTRIAL GROUP CO.,LTD.
TEL/WhatsApp: +86 18622096679
Mail: admin@coilwindingmachinechina.com
Web:www.coilwindingmachinechina.com

Processing Range

No.	Item Category	Value
1	Outer Diameter of Toroidal Core	16 ~ 40 mm
2	Height of Toroidal Core	23 mm
3	Wire Diameter	0.6 ~ 2.0 mm
4	Wire Length	Within 200 cm
5	Efficiency	0.8 ~ 3 s per turn
6	Winding Direction	Clockwise / Counter-clockwise winding available
7	Winding Layers	1 ~ 3 layers
8	Inner Bore	Ensure the full-winding hook needle can pass smoothly

Special Notes

The above processing range does not mean all products can be wound. The machine runs stably after commissioning, with daily operation rate＞95%. The whole machine is covered by a 1-year warranty; solenoid valves enjoy lifetime warranty.